

Manometri · Oleodinamica Serie LX

CARATTERISTICHE COSTRUTTIVE

Manometri per tutti i fluidi non corrosivi a temperature tra i -20 +80°C compatibili con rame e sue leghe (è sempre necessario indicare il fluido usato).
Movimento amplificatore di precisione in ottone.

Quadrante in alluminio verniciato a forno.

– cassa inox AISI 304.

Elemento manometrico:

– tubo Bourdon in lega di rame per pressioni da -1 a 40 bar.

– tubo a spirale in lega di rame per pressioni da 60 a 1000 bar.

Saldature in lega di stagno.

Grado di protezione Ip 65.

Particolarmente robusti, usati per sistemi idraulici, pompe, compressori, macchine utensili idropultrici, sistemi frigoriferi.



Pressure gauges · Hydraulics LX Series

CONSTRUCTIONAL FEATURES

Pressure gauges for all non-corrosive fluids at temperatures between -20 and +80 °C, compatible with copper and its alloys (always indicate the utilized fluid).

– stainless steel AISI 304 case.

Precision amplifier movement in brass.

Dial in stove-enamelled aluminium.

Pressure gauge parts:

– Bourdon tube in copper alloy for pressure ratings from -1 to 40 bar.

– spiral tube in copper alloy for pressure ratings from 60 to 1000 bar.

Welds in tin alloy.

Protection degree Ip 65.


Particularly sturdy, used for plumbing systems, pumps, compressors, machine tools, high pressure water cleaners, refrigerating systems.

DIMENSIONI E SISTEMA DI MONTAGGIO

DIMENSIONS AND ASSEMBLY SYSTEM

nom.	DIMENSIONI · Dimensions												
	a	b	c	d	e	f	g	h	i	l	m	n	o
63	58	76	46	68.5	9	62	87	75	3.6		6.5	79	

TIPO D
TYPE D



RACCORDI DI SERIE · Standard Threads

BSP DIN 16288			
1/8	1/4	3/8	1/2