

Hot water superservice 2SC blue

1/1



Composition:

- Inner tube: special synthetic rubber resistant to mineral, vegetable and hydraulic oil.
- Reinforcement: two braids of steel wire.
- Cover: synthetic rubber resistant to oil, abrasion and weather.

Working temperature: From -40° C to +155° C (peak).

Part n°	DN	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Bending radius (mm)	Weight (kg/m)
MSC0214A	1/4"	6,5	13,9	400	5.800	1.600	23.200	75	0,19
MSC0215A	5/16"	8,3	14,6	400	5.800	1.400	23.200	85	0,30
MSC0216A	3/8"	9,9	16,6	400	5.800	1.320	23.200	90	0,37
MSC0218A	1/2"	12,9	21	275	3.988	1.100	15.950	130	0.40
MDDSC0214A	1/4"	6,5	13,6	400	5.800	1.600	23.200	75	0,19
MDDSC0215A	5/16"	8,3	14,6	400	5.800	1.600	23.200	85	0,30
MDDSC0216A	3/8"	9,9	16	400	5.800	1.320	23.200	90	0,37
MDDSC0218A	1/2"	12,9	21	275	3.998	1.100	15.950	130	0,40